

# ES-512G Dental Unit







- Electric dental unit with synchronized movements: when the chair moves up or down, the hydraulic unit behaves accordingly to allow the spittoon to always be the same height of patient's head.
- Leather covered dental chair and wider cushion.
- Memory of 9 programmable positions + zero position
- Adjustable articulated headrest
- Built-in high/low suction system with separated circuits for surgical and saliva
- Adjustable LED operating lamp (10 bulbs, you can select 11000, 25000 or 36000 LUX)
- Easy to plug hand accessories for easy cleaning and disinfection
- Down-mounted instrument tray (Optional top mounted)
  - 5 instrument positions:
    - (3 way syringe + three hand pieces + one free)
  - X-ray film viewer (Optional LED panoramic version)
  - Soft keyboard for all commands and memories
- TM version with stainless steel adjustable tray placed under. Each instrument cable has five block-positions to facilitate work and after the fifth block, the cable rewinds
- Assistant section with 4 instrument positions (two saliva and surgical aspiration tubes with automatic switching + one 3 way syringe + one free)
- Automatic spittoon rinsing in zero chair position
- Outer tank for water and/or disinfection
- Ceramic spittoon with 90° swivel water supply arm. Automatic filling of the cup by light sensor, adjustable capacity.
- Built-in junction box
- Multi-functional footswitch



Cod. ES-512G DM Standard basic version of the dental unit, with down mounted instrument tray



Cod. ES-512G TM Optional luxury version of the dental unit, with top mounted instrument tray





# Standard configuration

## Main keyboard for:

- chair movements with 3 memorized positions + zero
- rinsing spittoon and manual filling cup
- light switch of the x-ray viewer
- water heating

### Assistant section with:

- aspiration and saliva canule, automatic switching
- 3-way syringe (hot/cold water)
- LED curing light (optional)

# Subsidiary keyboard for:

- chair movements and memory programs
- rinsing spittoon and manual filling cup
- heating water

### Ceramic spittoon

- rotatable water supply arm
- light sensor for automatic filling cup

# Outer tank

for outer water and disinfection

### Articulated arm with LED operating lamp adjustable light

# • Multi-functional foot controller

with patient positions, water supply rinsing/flushing and blowing for the hand-pieces

### • Built-in junction box



Main keyboard



Multi-functional footswitch



Assistant section with instrument tray and subsidiary keyboard



Articulated arm with LED operating lamp



Ceramic spittoon

# **Technical Specifications**

• Power voltage : 220 V / 50-60 Hz

• Motor voltage: 24 V

Water pressure : 0.2MPa-0.4MPaAir pressure : 0.5MPa-0.8MPa

• Package: wooden box 150x110x131h cm,

gross weight 300kg





# **Optional**

- LED panoramic x-ray film viewer
- LCD display for the unit status
- Operating halogen light 15000 LUX
- Endoscope system composed by:
  - CCD intra-oral camera
  - articulated arm with LCD colour screen
- Fiber optic predisposition for 1 or 2 instruments
- Electronic module for micromotor
- Built-in LED curing light
- Built-in electronic scaler with autoclavable handle
- High speed hand piece air and electronic powered
- Low speed hand piece air and electronic powered
- Operating stool
- Air compressor
- External junction box with water/air control pressure gauges and water/air/electric main on/off switch



**LED panoramic** x-ray film viewer



LCD display for the unit status



Operating halogen light



**Endoscope system** 



**Electronic module** for micromotor



**Built-in LED curing light** 





DISTRIBUTOR



Air compressor



**External junction box** 



Pulse Healthcare Technology House: 11/1, Shahid Minar Road Kallyanpur, Dhaka-1216, Bangladesh. Mobile: +8801708008061

e-mail: info@pht.com.bd web: www.pht.com.bd



ESSE3 srl, Via Garibaldi 30 14022 Castelnuovo D.B. (AT) Tel +39 011 99 27 706 Fax +39 011 99 27 506 e-mail esse3@chierinet.it web: www.esse3-medical.com

