

# ESMD-60

Laser Photocoagulator





# ESMD-60



## Laser Photocoagulator

# **Features**

#### -Compact

Compact and portable design for adavnced solid-state-laser technology Touchscreen operations for easier use

#### -Precise

Continuously zoomed and precise laser spot pooint Homogeneous photocoagulation spot retina Stable output but no power degeneration for closed-loop power control system

#### -Safe

Minimized power density on cornea Maximum protection while maintainig clear field view

## -Adaptable

Detachable delivery system, compatible with a range of slit lamp microscopes

# **Specifications**

#### **Treatment Beam**

Type: Diode-pumped frequency-doubled solid state laser

Wavelength: 532nm Green true CW Power output: 50~1200mW, adjustable Pulse duration: 0.01s~3s, adjustable Pulse interval: 0.05s~1s, adjustable

# **Aiming Beam**

Type: Laser diode

Wavelength: 630~680nm

Power output: <1.0mW, adjustable

Cooling: Air cooled, thermoelectric cooler system

Laser delivery unit: Slit lamp adapter

Slit lamp delivery: Haag Streit style slit lamp

Spot size: continuously adjustable from 50 to 500 microns

Power: 100-240VAC Size: 30x28x14 cm/



Pulse Healthcare Technology
House: 11/1 Shahid Minar Road

House: 11/1, Shahid Minar Road Kallyanpur, Dhaka-1216, Bangladesh.

Mobile: +8801708008061 e-mail: info@pht.com.bd web: www.pht.com.bd



