

## ES-AU-30L

STERILIZATION

Bench top steam sterilizer





## ES-AU-30L



## Bench top steam sterilizer



- Full-Automatic operation and door lock system
- Printer and USB port
- Automatic and safety door lock system
- According to Europe B standard, with 3 times pre-vacuum
- Failure reason displayed on LCD
- New type of separate steam generator
- Multi-language
- Detailed print with monitoring temperature and pressure record in 6 seconds.

Technical Features	
Chamber Dimensions	250×600 mm (Φ×D)
Chamber Capacity	30L
Overall Size	48×80×42 cm (L×W×H)
Heater	2000W
Net Weight	55 kg
Gross Weight	65 kg
Packing Size	94×57×50 cm
Minimum Desk Size	60×50 cm
Power Supply	220±10%,50HZ
Sterilize Temperature	121/134
Sterilization Time	4-18mins
Dry Procedure	Vacuum drying
Sterilizer Construction	Stainless steel 304
Clean Water tank	Internal
Stainless steel instrument container	5trays
Safety	<ul> <li>Over heat control: When inner temperature is overheated, power will be shut down automatically with an alarm system</li> </ul>
0188/80	<ul> <li>Over pressure control: alarm in case of over pressure.</li> </ul>

• Safety door lock system



## **Pulse Healthcare Technology**

House: 11/1, Shahid Minar Road Kallyanpur, Dhaka-1216, Bangladesh. Mobile: +8801708008061

e-mail: info@pht.com.bd web: www.pht.com.bd



• Low water level indictor: alarm in case of low water

ESSE3 srl, Via Garibaldi 30 14022 Castelnuovo D.B. (AT) Tel +39 011 99 27 706 Fax +39 011 99 27 506 e-mail esse3@chierinet.it web: www.esse3-medical.com

