

ESB-200S Infant Incubator





ESB-200S



Infant Incubator

Function features:

- Microprocessor based servo controlled temperature system
- · Integral timer to record therapy time
- · Air temperature and skin temperature control mode
- Alarm functions:

Power failure; Over temperature; Temperature deviation; Fan failure; Temperature sensor failure

- Skin temperature sensor fall protect function to avoid over temperature
- Air temperature, skin temperature, timer and heat power separately displayed by LED
- >37°C temperature setting
- Humidity adjustable continuously (not displayed)
- Oxygen port and RS-232 connector
- The infant bed inclination angle is adjustable
- A keypad lock prevent inadvertent changes the setting

Product main characteristic

- Trough for pulling and pushing ,which is convenient to add the water and wash
- Fan with low noise and long life-span
- Temperature deviation and over temperature could be amended in front panel directly
- · A second thermal cut-out function for more safety
- The infant bed inclination angle is adjustable
- Six operating windows, two side access operating windows can be swivelled
- · 4 drawers for easy storage



Main body(including the Transparent hood), Control system, Infant bed, Water trough), I.V. pole, Mattress, Drawers, Castors

Optional accessories

Electronic Elevator;

Power supply

Power input

Operating

conditions

Double wall hood; X ray cassette & Integrated scale; Upside LED phototherapy unit cod.BL-30D; Downside LED phototherapy unit cod.BL-100; Air/Oxygen Blender;



Double Wall Hood

X ray cassette & Integrated scale

20°C ~ 30°C

30%~75%RH



Upside LED phototherapy unit cod.BL-30D



Cod. ES-200S


Downside LED phototherapy



Air/Oxygen Blender



Electronic Elevator



Air circulation system



Air Temp. control range

Skin temp. control range

Uniformity of mattress

Temp. fluctuation

temperature

Skin temp. sensor accuracy ±0,3°C

1) Control unit and cabinet: 120x70x96cm N.W.:80Kg

2) Hood:97x56x63cm N.W.:15Kg



Pulse Healthcare Technology House: 11/1, Shahid Minar Road Kallyanpur, Dhaka-1216, Bangladesh.

Mobile: +8801708008061 e-mail: info@pht.com.bd web: www.pht.com.bd

Technical Features

Environment air velocity of flow < 0,3m/s

32°C~38.5°C

25°C~38°C

±0.5 °C

≤0,8°C

≤45min

≤55dB

65x37 cm

1200mL

0,5 um

±10°

420VA

Environment temperature

Environment relative humidity

AC 110/220V 60/50Hz



ESSE3 srl, Via Garibaldi 30 14022 Castelnuovo D.B. (AT) Tel +39 011 99 27 706 Fax +39 011 99 27 506 e-mail esse3@chierinet.it web: www.esse3-medical.com

